



SHEPHERD DISTRIBUTION CO.

## POLY CLOSE-UP FILM

<u>NAME</u>	<u>THICKNESS*</u>
Super Rawhide 2.5	2.5 Mil
Super Rawhide 3.0	3.0 Mil
Super Rawhide 3.5	3.5 Mil
Super Rawhide 4.0	4.0 Mil
Super Rawhide 4.5	4.5 Mil
Super Rawhide 5.0	5.0 Mil
Super Rawhide 5.5	5.5 Mil
Super Rawhide 6.0	6.0 Mil
Super Rawhide 6.5	6.5 Mil
Super Rawhide 7.0	7.0 Mil
Super Rawhide 10.0	10.0 Mil

**ALSO AVAILABLE: SHRINKWRAP CLOSE-UP TO 30' WIDE**

All White Close-Up Poly contains UVI inhibitors.

\*Thickness tolerance is  $\pm 10\%$

Poly available plain or with single color printed logo and in widths to 30'



SHEPHERD DISTRIBUTION CO.

## SUPER RAWHIDE

### CLOSE-UPS

#### TECHNICAL DATA SHEET

General Specifications:

Color White

Mechanical Properties:

<u>Item</u>	<u>Score</u>	<u>Units</u>	<u>ASTM#</u>
Dart Test	150	grams	1709
Tensile Yield			882
MD	2000	lb/in <sup>2</sup>	
TD	1600	lb/in <sup>2</sup>	
Stiffness Yield			
MD	24	Relative Index	
TD	14	Relative Index	
Tensile Break			882
MD	3500	lb/in <sup>2</sup>	
TD	3200	lb/in <sup>2</sup>	
Stiffness Break			
MD	2.7	Relative Index	
TD	1.9	Relative Index	
Elongation			882
MD	700	%	
TD	900	%	