

SELF-ADHESIVE **SHINGLE STARTER**TM

MFM Building Products Corp. manufactures a wide range of innovative waterproofing products for the building industry. Proven through many years of use in the field, MFM products are engineered for superior performance and ease of installation.

DESCRIPTION

MFM ShingleStarterTM is a self-adhesive membrane that eliminates the need to cut shingle tabs. ShingleStarter comes with a seal strip to prevent wind uplift at the roof edge. The peel and stick application allows fast installation, saving time and labor. The membrane is waterproof and self-sealing around nails and other penetrations. ShingleStarter may be adhered directly to the roof deck or to Wind & Water SealTM self-adhering underlayments.

SURFACE PREPARATION

1. The surface to receive ShingleStarter must be clean, smooth and dry.
2. Remove old shingles, nails and debris before applying ShingleStarter.

Application Range	50°F-110°F
Color	Black
Roll Length	33.5'
Roll Width	7.2"
Carton Weight	59lbs
Area/Roll	20.1 ft²

PROPERTY	TEST METHOD	RESULTS
Thickness	ASTM D 1970	40 mils Min.
Pliability	ASTM D 1970	Pass
Nail Sealability	ASTM D 1970	Pass

INSTALLATION

1. Prepare the surface for application.
2. Only apply as much ShingleStarter as will be covered by shingles the same day.
3. Making sure the seal strip is toward the eave, carefully align ShingleStarter with the eave edge, remove the release liner and press the product in place. (Figure 1)
4. If using a drip edge ShingleStarter should be installed flush with the bottom edge of the drip edge with the first course of shingles installed per the shingle manufacture instructions.
5. When going from one roll to another, overlap 6 inches.
6. Continue installing shingle courses.
7. When applying ShingleStarter up the rake align at rakes edge, remove release liner and press into place.
8. If ShingleStarter is being applied in temperatures below 50° F, it may be necessary to spot nail the product in place. ShingleStarter will adhere to the deck and shingle as weather warms.

PACKAGING

ShingleStarter is shipped in cartons of 8 individually wrapped rolls that are 7.2" X 33.5'.

STORAGE

Store rolls in a dark, dry place in original shipping carton if possible. Protect rolls from moisture and physical damage. Keep in a heated building during cold weather and protect from temperatures exceeding 100° F. Do not unwrap rolls until applied.

WARNINGS

- Apply ShingleStarter only on areas that will receive shingles the same day – airborne dirt and debris can affect the seal tab's ability to properly seal to the shingle.
- Avoid falls when using ladders and scaffolding.
- Be sure any surface to receive ShingleStarter is structurally sound and will support the weight of the installer and any anticipated load.
- When applying ShingleStarter in temperatures below 50° F, the product must be nailed to hold it in place. Adhesion to the deck and shingle will occur as the deck warms.

Figure 1




Figure 2

