

Sherwin-Williams®
NR4000
Siliconized Acrylic Latex Caulk

Physical Properties:

Type:	100% Pure Acrylic with Silicone
Colors:	Bright White
Shelf Life:	12 months
Flash Point:	N/A (Water based)
Flammability:	N/A (Water based)
Cure Time:	5-7 days at 75°F
Tack Free Time:	12 minutes at 75°F
Application Temperature:	Above 40°F
Service Temperature:	-30°F to 180°F
VOC Level:	.20 lbs./gal
Mildew Resistance:	Good
Water Resistance:	Good
Odor:	Low
Shrinkage:	Low/Moderate
Vehicle:	Water
Solids by Weight:	83.5 ± 1%
Weight/Gallon:	13.2 ± 0.2 lb.
Painting:	After 2 hours

Performance Data:

Joint Movement Capability:	Good
Joint Size:	No larger than ½" x ½"
Freeze-Thaw Stability:	Stable through 5 cycles
Clean Up:	Water
Flexibility:	Excellent
Durability:	40 Years

Surface Preparation: Surface to be sealed should be clean, dry and free from oils, loose mortar, laitance, form release agents, old caulking, old paint, or other contaminants. Allow new concrete to cure for 30 days before caulking.

Cautions: Contains Crystalline Silica. Use only with adequate ventilation. Avoid contact with eyes and skin. Wash hands after using. Do not transfer contents to other containers for storage.

Limitations: Do not use under water. Do not use in areas subject to water immersion. Keep from freezing.

Specification Compliance: Sherwin-Williams® NR4000 meets performance requirements of ASTM Standard C-834.

Packaging:

Color	SMIS #	UPC	Size
Bright White	162-7595	0-23275-00650-8	10.0 fl. oz.

For more information please call or write:

The Sherwin-Williams Co.
101 Prospect Ave. NW
Cleveland, OH 44115
1-800-241-5295 option 1 Customer Service
1-800-241-5295 option 2 Technical Service

Dymnt # 200-5666
Diversified Brands # WP0009513