

White Lightning® WL6000 Subfloor Adhesive

Physical Properties: WL6000 Subfloor Adhesive

Type:	Solvent-Based Adhesive	Service Temperature:	-30°F to 175°F
Color:	Tan	Storage Temperature:	-30°F to 175°F
Shelf Life:	12 Months	VOC Level:	394.1 g/l
Flash Point:	Less Than 0°F	Vehicle:	Thermo-Plastic Rubber
Open Time:	0-20 Minutes	Weight Solids:	66%
Full Cure Time:	24 Hours	Weight/Gallon:	9.1 lbs/gal
Application Temperature:	Above 0°F	Consistency:	Gun-Grade Mastic

Performance Data:

Clean-Up:	Clean Tools with Mineral Spirits
Water Resistance:	Excellent
Linear Coverage:	
10 oz Cartridge	
3/8" Bead Application	11.5 ft
29 oz Cartridge	
3/8" Bead Application	33.4 ft

Product Description:

White Lightning® WL6000 Panel Construction Adhesive is a high performance adhesive.

Basic Uses:

WL6000 is a heavy-duty adhesive for installation and repair of flooring applications such as subfloors, tongue & groove floors, decks, ramps, porches, steps and stairs. Can be used on metal, fiberglass, fiberboard, slate, hardboard, drywall, plastic foams (except polystyrene), masonry and wet, frozen and chemically pressure treated/untreated lumber.

Surface Preparation:

Surface should be clean, dry, free from oils, dirt, old caulking, old paint or other contaminants. Precut all lumber to size and prepare all other installation materials before applying adhesive.

Cautions:

Contents are EXTREMELY FLAMMABLE. Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively. During use, and until all vapors are gone: Keep area ventilated. Do not smoke. Extinguish all flames, pilot lights and heaters. Turn off stoves, electric tools and appliances, and any other sources of ignition.

Contains: CRYSTALLINE SILICA, HEXANE AND TOLUENE. VAPOR HARMFUL. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. Avoid contact with eyes and skin. Wash hands after using. Do not transfer to other containers for storage.

Limitations:

Do not apply at temperatures below 0°F. Do not use on tub kits. Do not use on rigid plastics or polystyrene foam.

Specifications:

Certified to exceed performance requirements of the American Plywood Association Specification AFG-01 for Field-Gluing Plywood to Wood Framing. Approved by HUD-FHA.



For more information please call or write:

White Lightning® Products • 101 Prospect Ave. NW • Cleveland, OH 44115
1-800-241-5295 Option 1 Customer Service • 1-800-241-5295 Option 2 Technical Service
www.wlcaulk.com