

Sherwin-Williams®
NR5000
Siliconized Acrylic Latex Caulk

Physical Properties:

Type:	100% Pure Acrylic with Silicone
Color:	Bright White
Shelf Life:	12 months
Flash Point:	N/A (Water based)
Flammability:	N/A (Water based)
Cure Time:	5 to 7 days at 75°F
Tack Free Time:	12 minutes at 75°F
Application Temperature:	Above 40°F
Service Temperature:	-30°F o 180°F
VOC Level:	.13 lbs./gal
Mildew Resistance:	Good
Water Resistance:	Good
Odor:	Low
Shrinkage:	Low/Moderate
Vehicle:	Water
Solids by Weight:	82.5 ± 1%
Weight/Gallon:	13.15 ± 0.2 lb.

Performance Data:

Joint Movement Capability:	Good
Joint Size:	No larger than ½" X ½"
Freeze-Thaw Stability:	Stable through 5 cycles
Durability:	50 Years
Clean Up:	Water
Flexibility:	Excellent

Surface Preparation: Clean surface free from oils, dirt, old caulking, old paint or other contaminants.

Application Conditions: Apply at temperatures above 40°F. Never use in butt joints, joints subject to heavy abrasion and wear or those that are frequently under water. Do not apply when rain or moisture is expected.

Painting: A minimum of 2 hours dry time is needed before applying latex or oil-based paint. Allow extra dry time during periods of high humidity or cool temperatures.

Cautions: Contains Crystalline Silica. Use only with adequate ventilation. Avoid contact with eyes and skin. Wash hands after using. Do not transfer contents to other containers for storage.

Specification Compliance: Exceeds ASTM Spec. C-834; exceeds ASTM-C-920, Class 12.5 Specifications and exceeds Federal Spec. TT-S-00230C Class B.

Limitations: Do not use under water. Do not use in areas subject to water immersion. Keep from freezing.

Packaging:

Color	Part #	SMIS#	UPC	Size
Bright White	WL000660A	162-7728	0-23275-00660-	10.1 fl oz.

For more information please call or write:
White Lightning Products
101 Prospect Ave. NW
Cleveland, OH 44115
1-800-241-5295

Dyment # 200-5665
Diversified Brands # WP0009514